



Transport
for NSW

South Batemans Bay Link Road

Water Monitoring Report

01/05/2023

Contents

- 1 Environmental Monitoring 4
 - 1.1 1.1 Background 4
 - 1.2 1.2 Methodology 4
- 2 Project Rainfall and Monitoring Update 5
 - 2.1 Project to Date (October 2021 to Apr 2023)..... 5
 - 2.2 Project Update Apr 2023 5
- 3 SBBLR RAINFALL RECORD 6
- 4 SBBLR WATER MONITORING REGISTER 7

1 Environmental Monitoring

1.1 Background

The South Batemans Bay Link Road operates under an Environmental Protection Licence (EPL21590). Under the conditions of the licence the project is required to monitor water quality at specified locations near the project.

1.2 Methodology

To maintain compliance with the Licence the project team has developed a Water Monitoring Program and Response Plan.

Water monitoring is completed by taking samples at specified locations following a rainfall event that exceeds the 5 days 85th percentile event as noted in the Blue Book which is 37.4mm in Batemans Bay. If a breach of the Erosion and Sediment Controls is identified, water monitoring will also be undertaken and an Environmental Report Raised.

Water samples are tested on site for Oil and Grease, pH, Total Suspended Solids Turbidity and Conductivity and results are recorded in a register. ½ litre of water samples are sent to a laboratory to confirm the Total Suspended Solids result.

2 Project Rainfall and Monitoring Update

2.1 Project to Date (October 2021 to April 2023)

Between the commencement of the project in **October 2021 and April 2023** the project has experienced a significant amount of rainfall.

Total rainfall recorded on site during this period is **2,395 mm**


The Water Monitoring program was implemented in November 2021 when the Erosion and Sediment Controls were installed, vegetation clearing, and earthworks activities commence. Between October 2021 and Apr 2023, the water monitoring requirement was triggered 19 times (samples were sent lab)

2.2 Project Update Apr 2023

During the month of Apr'23 there was **64 mm** of rain recorded on site. The Water Monitoring requirement was triggered once during the month of Apr'23.

3 SBBLR RAINFALL RECORD

SBBLR - Monthly Vs Average Rainfall at Batemans Bay
27th Apr 2023 - PTD (2395 mm Vs 1470 mm)



4 SBBLR WATER MONITORING REGISTER

5 LAB REPORTS



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 285756

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	20/12/2021
Date completed instructions received	20/12/2021

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 04/01/2022

Date of Issue 24/12/2021

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics				
Our Reference		285756-1	285756-2	285756-3
Your Reference	UNITS	HRCD1	HRCD2	MCU2
Date Sampled		16/12/2021	16/12/2021	16/12/2021
Type of sample		Water	Water	Water
Date prepared	-	23/12/2021	23/12/2021	23/12/2021
Date analysed	-	23/12/2021	23/12/2021	23/12/2021
Total Suspended Solids	mg/L	24	12	10

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			23/12/2021	1	23/12/2021	23/12/2021		23/12/2021	[NT]
Date analysed	-			23/12/2021	1	23/12/2021	23/12/2021		23/12/2021	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	24	28	15	97	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 286793

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	6 Water
Date samples received	17/01/2022
Date completed instructions received	17/01/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Please refer to the last page of this report for any comments relating to the results.

Report Details

Date results requested by 24/01/2022

Date of Issue 27/01/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics						
Our Reference		286793-1	286793-2	286793-3	286793-4	286793-5
Your Reference	UNITS	HRCD1	HRCD2	MCU2	HRCD1	HRCD2
Date Sampled		06/01/2022	06/01/2022	06/01/2022	12/01/2022	12/01/2022
Type of sample		Water	Water	Water	Water	Water
Date prepared	-	18/01/2022	18/01/2022	18/01/2022	18/01/2022	18/01/2022
Date analysed	-	18/01/2022	18/01/2022	18/01/2022	18/01/2022	18/01/2022
Total Suspended Solids	mg/L	<5	18	210	<5	18

Miscellaneous Inorganics		
Our Reference		286793-6
Your Reference	UNITS	MCU2
Date Sampled		12/01/2022
Type of sample		Water
Date prepared	-	18/01/2022
Date analysed	-	18/01/2022
Total Suspended Solids	mg/L	20

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			18/01/2022	1	18/01/2022	18/01/2022		18/01/2022	[NT]
Date analysed	-			18/01/2022	1	18/01/2022	18/01/2022		18/01/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	<5	<5	0	96	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

Report Comments

Samples received in good order: Holding time exceedance



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto
Contact Person: Chris Bearzatto
Project Mgr: Chris Bearzatto
Sampler: Sri Naidu
Address:
153 Auckland Street, Bega NSW 2550
Phone: (02) 6492 9505 **Mob:** 0438 636 492
Email:
Chris.Bearzatto@transport.nsw.gov.au;

Client Project Name / Number / Site etc (ie report title):
Batemans Bay Link Road
PO No.: Credit Card
Envirolab Quote No. : Quote request issued 17/12 to D. Springer
Date results required: Standard Testing Time
Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply
Report format: esdat / equis /
Lab Comments:

Sample information **Tests Required** **Comments**

Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water															Provide as much information about the sample as you can
1	HRC1	100mm	06/01/2022	Water	✓															
2	HRC2	100mm	06/01/2022	Water	✓															
3	MCU2	100mm	06/01/2022	Water	✓															
1	HRC1	100mm	12/01/2022	Water	✓															
2	HRC2	100mm	12/01/2022	Water	✓															
3	MCU2	100mm	12/01/2022	Water	✓															

12 Ashley St, Chatswood NSW 2067
 Ph: (02) 9910 6200
Job No: 286793
Date Received: 17/1/2022
Time Received: 1430
Received By: R
Temp: Cool/Ambient: 26°C
Cooling: Icepack
Security: Inactivated

Relinquished by (Company): Transport for NSW
Print Name: Sri Naidu
Date & Time: 12/01/2022
Signature: *[Signature]*

Received by (Company): ES
Print Name: Ray
Date & Time: 12/1/2022 1430
Signature: *[Signature]*

Lab use only:
Samples Received: Cool or Ambient (circle one)
Temperature Received at: 26°C (if applicable)
Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 291208

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto, Sri Naidu
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	9 Water
Date samples received	17/03/2022
Date completed instructions received	17/03/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 24/03/2022

Date of Issue 23/03/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Diego Bigolin, Inorganics Supervisor

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics						
Our Reference		291208-1	291208-2	291208-3	291208-4	291208-5
Your Reference	UNITS	MCU - West PHWY	HRCD1 - Bridge	HRCD2 - Track	MCU - West PHWY	HRCD1 - Bridge
Date Sampled		27/02/2022	27/02/2022	27/02/2022	04/03/2022	04/03/2022
Type of sample		Water	Water	Water	Water	Water
Date prepared	-	22/03/2022	22/03/2022	22/03/2022	22/03/2022	22/03/2022
Date analysed	-	22/03/2022	22/03/2022	22/03/2022	22/03/2022	22/03/2022
Total Suspended Solids	mg/L	24	36	30	23	26

Miscellaneous Inorganics					
Our Reference		291208-6	291208-7	291208-8	291208-9
Your Reference	UNITS	HRCD2 - Track	MCU - West PHWY	HRCD1 - Bridge	HRCD2 - Track
Date Sampled		04/03/2022	09/03/2022	09/03/2022	09/03/2022
Type of sample		Water	Water	Water	Water
Date prepared	-	22/03/2022	22/03/2022	22/03/2022	22/03/2022
Date analysed	-	22/03/2022	22/03/2022	22/03/2022	22/03/2022
Total Suspended Solids	mg/L	6	6	14	24

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			22/03/2022	1	22/03/2022	22/03/2022		22/03/2022	[NT]
Date analysed	-			22/03/2022	1	22/03/2022	22/03/2022		22/03/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	24	21	13	85	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto

Contact Person: Chris Bearzatto

Project Mgr: Chris Bearzatto

Sampler: Sri Naidu

Address:
153 Auckland Street, Bega NSW 2550

Phone: (02) 6492 9505 **Mob:** 0438 636 492

Email:
Chris.Bearzatto@transport.nsw.gov.au

Client Project Name / Number / Site etc (ie report title):
Batemans Bay Link Road

PO No.: Credit Card

Envirolab Quote No.: Quote request issued 17/12 to D. Springer

Date results required: Standard Testing Time

Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply

Report format: esdat / equis /

Lab Comments:

Sample information					Tests Required										Comments						
Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water																Provide as much information about the sample as you can
1	1	MCU - West PHWY	27/02/2022	Water	✓																
2	2	HRC1 - Bridge	27/02/2022	Water	✓																
3	3	HRC2 - Track	27/02/2022	Water	✓																
4	1	MCU - West PHWY	04/03/2022	Water	✓																Lab ID: 24-1208
5	2	HRC1 - Bridge	04/03/2022	Water	✓																17-3-22
6	3	HRC2 - Track	04/03/2022	Water	✓																Time Received: 1400 By: JHAW
7	1	MCU - West PHWY	09/03/2022	Water	✓																Temp: Cool/Ambient
8	2	HRC1 - Bridge	09/03/2022	Water	✓																Security: Int
9	3	HRC2 - Track	09/03/2022	Water	✓																

Relinquished by (Company): Transport for NSW

Print Name: Chris Bearzatto

Date & Time: 10/3/22 2.00PM

Signature: *[Signature]*

Received by (Company): e v s s y o

Print Name: *[Signature]*

Date & Time: 17-3-22 @ 1400

Signature: *[Signature]*

Lab use only:

Samples Received: Cool or Ambient (circle one)

Temperature Received at: 13 (if applicable)

Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 293689

Client Details

Client	Transport of NSW
Attention	Chris Bearzatto, Sri Naidu
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	20/04/2022
Date completed instructions received	20/04/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Please refer to the last page of this report for any comments relating to the results.

Report Details

Date results requested by 28/04/2022

Date of Issue 02/05/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics				
Our Reference		293689-1	293689-2	293689-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Date Sampled		10/04/2022	10/04/2022	10/04/2022
Type of sample		Water	Water	Water
Date prepared	-	27/04/2022	27/04/2022	27/04/2022
Date analysed	-	27/04/2022	27/04/2022	27/04/2022
Total Suspended Solids	mg/L	8	14	22

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			27/04/2022	1	27/04/2022	27/04/2022		27/04/2022	[NT]
Date analysed	-			27/04/2022	1	27/04/2022	27/04/2022		27/04/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	8	9	12	91	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

Report Comments

Samples were out of the recommended holding time for this analysis.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 /
melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 /
brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 /
adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto

Contact Person: Chris Bearzatto

Project Mgr: Chris Bearzatto

Sampler: Sri Naidu

Address:
153 Auckland Street, Bega NSW 2550

Phone: (02) 6492 9505 **Mob:** 0438 636 492

Email:
Chris.Bearzatto@transport.nsw.gov.au;

Client Project Name / Number / Site etc (ie report title):
Batemans Bay Link Road

PO No.: Credit Card

Envirolab Quote No.: Quote request issued 17/12 to D. Springer

Date results required: Standard Testing Time

Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply

Report format: esdat / equis /

Lab Comments:

Sample Information					Tests Required										Comments					
Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water															Provide as much information about the sample as you can
1	MCU	100mm	10/04/2022	Water	✓															
2	HRCD1	100mm	10/04/2022	Water	✓															
3	HRCD2	100mm	10/04/2022	Water	✓															

ENVIROLAB
12 Ashley St,
Chatswood NSW 2067
Ph: (02) 9910 6200

Job No: 293689

Date Received: 20/04/22

Time Received: 1200

Received by: *CH*

Temp: Cool/Ambient

Cooling: Ice/No pack

Security: Intact/Broken *None*

Relinquished by (Company): Transport for NSW

Print Name: Chris Bearzatto

Date & Time: 13/04/2022 9.00 AM

Signature: *[Signature]*

Received by (Company): FLSSTD

Print Name: Chris Fine

Date & Time: 20/04/22 1200

Signature: *[Signature]*

Lab use only:

Samples Received: Cool/Ambient (circle one)

Temperature Received at: 18°C (if applicable)

Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 295871

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland St, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	19/05/2022
Date completed instructions received	19/05/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Please refer to the last page of this report for any comments relating to the results.

Report Details

Date results requested by 26/05/2022

Date of Issue 26/05/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics				
Our Reference		295871-1	295871-2	295871-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Date Sampled		13/05/2022	13/05/2022	13/05/2022
Type of sample		Water	Water	Water
Date prepared	-	25/05/2022	25/05/2022	25/05/2022
Date analysed	-	25/05/2022	25/05/2022	25/05/2022
Total Suspended Solids	mg/L	<5	56	110

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			25/05/2022	1	25/05/2022	25/05/2022		25/05/2022	[NT]
Date analysed	-			25/05/2022	1	25/05/2022	25/05/2022		25/05/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	<5	<5	0	92	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

Report Comments

Total suspended solids have exceeded the recommended technical holding times, Envirolab Group form 347 "Recommended Preservation and Holding Times" can be provided on request (available on the Envirolab website)



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 300859

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland St, Bega, NSW

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	20/07/2022
Date completed instructions received	20/07/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 27/07/2022

Date of Issue 27/07/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics				
Our Reference		300859-1	300859-2	300859-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Date Sampled		4/07/2022	4/07/2022	4/07/2022
Type of sample		Water	Water	Water
Date prepared	-	25/07/2022	25/07/2022	25/07/2022
Date analysed	-	25/07/2022	25/07/2022	25/07/2022
Total Suspended Solids	mg/L	<5	290	340

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			25/07/2022	3	25/07/2022	25/07/2022		25/07/2022	[NT]
Date analysed	-			25/07/2022	3	25/07/2022	25/07/2022		25/07/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	3	340	340	0	118	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 307191

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland St, Bega, NSW

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	04/10/2022
Date completed instructions received	04/10/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 11/10/2022

Date of Issue 11/10/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Diego Bigolin, Inorganics Supervisor

Authorised By

Nancy Zhang, Laboratory Manager

Miscellaneous Inorganics				
Our Reference		307191-1	307191-2	307191-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Depth		0.1	0.1	0.1
Date Sampled		26/09/2022	26/09/2022	26/09/2022
Type of sample		Water	Water	Water
Date prepared	-	11/10/2022	11/10/2022	11/10/2022
Date analysed	-	11/10/2022	11/10/2022	11/10/2022
Total Suspended Solids	mg/L	<5	330	510

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			11/10/2022	2	11/10/2022	11/10/2022		11/10/2022	[NT]
Date analysed	-			11/10/2022	2	11/10/2022	11/10/2022		11/10/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	2	330	360	9	87	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - EnviroLab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au


Melbourne Lab - EnviroLab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au


Brisbane Office - EnviroLab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au


Adelaide Office - EnviroLab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto
Contact Person: Chris Bearzatto
Project Mgr: Chris Bearzatto
Sampler: Sri Naidu
Address:
 153 Auckland Street, Bega NSW 2550
Phone: (02) 6492 9505 **Mob:** 0438 636 492
Email:
 Chris.Bearzatto@transport.nsw.gov.au

Client Project Name / Number / Site etc (ie report title):
 Batemans Bay Link Road
PO No.: Credit Card
EnviroLab Quote No.: Quote request issued 17/12 to D. Springer
Date results required: Standard Testing Time
Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply
Report format: esdat / equis /
Lab Comments:

Sample information					Tests Required										Comments						
EnviroLab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water																Provide as much information about the sample as you can
1	MCU	100mm	26/09/2022	Water	✓																MCU 35°43'55" S 150°10'03" E - West
2	HRCDD1	100mm	26/09/2022	Water	✓																HRCDD (1) 35°43'47" S 150°10'33" E - Bridge
3	HRCDD2	100mm	26/09/2022	Water	✓																HRCDD (1) 35°43'47" S 150°10'33" E - Track
					 <p>EnviroLab Services 12 Ashley St Chatswood NSW 2067 Ph 02 9910 6200</p> <p>Job No: 307191 9-10-22 Date Received: 13/10/22 Time Received: 13:15 Received By: JHAN Temp: Cool/Ambient Cooling: Ice/Icepack Security: Intact/Broken: None</p>																

Relinquished by (Company): Transport for NSW
Print Name: Chris Bearzatto
Date & Time: 28/09/22
Signature: 

Received by (Company): GCS SMD
Print Name: JHAN
Date & Time: 4.10.22 13:15
Signature: 

Lab use only:
Samples Received: Cool or Ambient (circle one)
Temperature Received at: 10 (if applicable)
Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 307652

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland St, Bega, NSW

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	6 Water
Date samples received	10/10/2022
Date completed instructions received	10/10/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 17/10/2022

Date of Issue 24/10/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Diego Bigolin, Inorganics Supervisor

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics

Our Reference		307652-1	307652-2	307652-3	307652-4	307652-5
Your Reference	UNITS	MCU-West PHWY	HRCD1- Bridge	HRCD2- Track	MCU- West PHWY	HRCD1- Bridge
Depth		100	100	100	100	100
Date Sampled		30/09/2022	30/09/2022	30/09/2022	02/10/2022	02/10/2022
Type of sample		Water	Water	Water	Water	Water
Date prepared	-	17/10/2022	17/10/2022	17/10/2022	17/10/2022	17/10/2022
Date analysed	-	17/10/2022	17/10/2022	17/10/2022	17/10/2022	17/10/2022
Total Suspended Solids	mg/L	<5	45	15	<5	11

Miscellaneous Inorganics

Our Reference		307652-6
Your Reference	UNITS	HRCD2- Track
Depth		100
Date Sampled		02/10/2022
Type of sample		Water
Date prepared	-	17/10/2022
Date analysed	-	17/10/2022
Total Suspended Solids	mg/L	8

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			17/10/2022	4	17/10/2022	17/10/2022		17/10/2022	[NT]
Date analysed	-			17/10/2022	4	17/10/2022	17/10/2022		17/10/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	4	<5	5	0	88	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 /
melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 /
brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 /
adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto
Contact Person: Chris Bearzatto
Project Mgr: Chris Bearzatto
Sampler: Sri Naidu
Address:
153 Auckland Street, Bega NSW 2550
Phone: (02) 6492 9505 **Mob:** 0438 636 492
Email: Chris.Bearzatto@transport.nsw.gov.au

Client Project Name / Number / Site etc (ie report title):
Batemans Bay Link Road
PO No.: Credit Card
Envirolab Quote No.: Springer
Date results required: Standard Testing Time
Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply
Report format: esdat / equis /
Lab Comments:

Sample information						Tests Required										Comments					
Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water																Provide as much information about the sample as you can
1	MCU - West PHWY	100 mm	30/09/2022	Water	✓																
2	HRC1 - Bridge	100 mm	30/09/2022	Water	✓																
3	HRC2 - Track	100 mm	30/09/2022	Water	✓																
4	MCU - West PHWY	100 mm	02/10/2022	Water	✓																
5	HRC1 - Bridge	100 mm	02/10/2022	Water	✓																
6	HRC2 - Track	100 mm	02/10/2022	Water	✓																

ENVIROLAB GROUP
Envirolab Services
12 Ashley St
Chatswood NSW 2067
Ph (02) 9910 6200
Job No: 307052
Date Received: 10/10/22
Time Received: 1330
Received by: [Signature]
Temp: Cool/Ambient
Cooling: Ice/Repack
Security: Intact/Broken/None

Relinquished by (Company): Transport for NSW
Print Name: Chris Bearzatto
Date & Time: 4/10/2022
Signature: [Signature]

Received by (Company): ELS 570
Print Name: Christine
Date & Time: 10/10/22 1330
Signature: [Signature]

Lab use only:
Samples Received: Cool or Ambient (circle one)
Temperature Received at: 18°C (if applicable)
Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 307851

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland Street,, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	12/10/2022
Date completed instructions received	12/10/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 19/10/2022

Date of Issue 24/10/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Miscellaneous Inorganics				
Our Reference		307851-1	307851-2	307851-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Depth		100	100	100
Date Sampled		07/10/2022	07/10/2022	07/10/2022
Type of sample		Water	Water	Water
Date prepared	-	19/10/2022	19/10/2022	19/10/2022
Date analysed	-	19/10/2022	19/10/2022	19/10/2022
Total Suspended Solids	mg/L	7	14	24

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			19/10/2022	1	19/10/2022	19/10/2022		19/10/2022	[NT]
Date analysed	-			19/10/2022	1	19/10/2022	19/10/2022		19/10/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	7	8	13	95	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au


Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto	Client Project Name / Number / Site etc (ie report title):
Contact Person: Chris Bearzatto	Batemans Bay Link Road
Project Mgr: Chris Bearzatto	PO No.: Credit Card
Sampler: Sri Naidu	Envirolab Quote No. : Quote request issued 17/12 to D. Springer
Address: 153 Auckland Street, Bega NSW 2550	Date results required: Standard Testing Time
Phone: (02) 6492 9505 Mob: 0438 636 492	Or choose: standard
Email: Chris.Bearzatto@transport.nsw.gov.au;	<i>Note: Inform lab in advance if urgent turnaround is required - surcharges apply</i>
	Report format: esdat / equis /
	Lab Comments:

Sample information					Tests Required										Comments					
Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water															Provide as much information about the sample as you can
1	MCU	100mm	07/10/2022	Water	✓															MCU 35°43'55" S 150°10'03" E - West
2	HRC1	100mm	07/10/2022	Water	✓															HRC1 (1) 35°43'47" S 150°10'33" E - Bridge
3	HRC2	100mm	07/10/2022	Water	✓															HRC2 (2) 35°43'47" S 150°10'33" E - Track
					 Envirolab Services 12 Ashley St Chatswood NSW 2067 Ph: (02) 9910 6200 Job No: 307851 Date Received: 12/10/22 Time Received: 1225 Received By: <u>UW</u> Temp: Cool/Ambient Cooling: Ice/Icepack Security: Intact/Broken/None															

Relinquished by (Company): Transport for NSW	Received by (Company): EW SYD	Lab use only:
Print Name: Bryan McMahon	Print Name: Katy Wayne	Samples Received: Cool or Ambient (circle one)
Date & Time: 7/10/2022	Date & Time: 12/10/22 1225	Temperature Received at: 18°C (if applicable)
Signature: <u>[Signature]</u>	Signature: <u>[Signature]</u>	Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 307931

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	3 Water
Date samples received	13/10/2022
Date completed instructions received	13/10/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 20/10/2022

Date of Issue 20/10/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Miscellaneous Inorganics				
Our Reference		307931-1	307931-2	307931-3
Your Reference	UNITS	MCU	HRCD1	HRCD2
Depth		100	100	100
Date Sampled		10/10/2022	10/10/2022	10/10/2022
Type of sample		Water	Water	Water
Date prepared	-	20/10/2022	20/10/2022	20/10/2022
Date analysed	-	20/10/2022	20/10/2022	20/10/2022
Total Suspended Solids	mg/L	6	18	22

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics					Duplicate			Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			20/10/2022	1	20/10/2022	20/10/2022		20/10/2022	[NT]
Date analysed	-			20/10/2022	1	20/10/2022	20/10/2022		20/10/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	1	6	6	0	86	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 309073

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland St, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	6 Water
Date samples received	27/10/2022
Date completed instructions received	27/10/2022

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 03/11/2022

Date of Issue 03/11/2022

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics

Our Reference		309073-1	309073-2	309073-3	309073-4	309073-5
Your Reference	UNITS	MCU	HRCD1	HRCD2	MCU	HRCD1
Depth		100	100	100	100	100
Date Sampled		24/10/2022	24/10/2022	24/10/2022	25/10/2022	25/10/2022
Type of sample		Water	Water	Water	Water	Water
Date prepared	-	03/11/2022	03/11/2022	03/11/2022	03/11/2022	03/11/2022
Date analysed	-	03/11/2022	03/11/2022	03/11/2022	03/11/2022	03/11/2022
Total Suspended Solids	mg/L	12	60	69	18	69

Miscellaneous Inorganics

Our Reference		309073-6
Your Reference	UNITS	HRCD2
Depth		100
Date Sampled		25/10/2022
Type of sample		Water
Date prepared	-	03/11/2022
Date analysed	-	03/11/2022
Total Suspended Solids	mg/L	56

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			03/11/2022	5	03/11/2022	03/11/2022		03/11/2022	[NT]
Date analysed	-			03/11/2022	5	03/11/2022	03/11/2022		03/11/2022	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	5	69	80	15	91	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au


Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto	Client Project Name / Number / Site etc (ie report title):
Contact Person: Chris Bearzatto	Batemans Bay Link Road
Project Mgr: Chris Bearzatto	PO No.: Credit Card
Sampler: Sri Naidu	Envirolab Quote No.: Quote request issued 17/12 to D. Springer
Address: 153 Auckland Street, Bega NSW 2550	Date results required: <u>Standard Testing Time</u> Or choose: standard <i>Note: Inform lab in advance if urgent turnaround is required - surcharges apply</i>
Phone: (02) 6492 9505 Mob: 0438 636 492	Report format: esdat / equis /
Email: Chris.Bearzatto@transport.nsw.gov.au;	Lab Comments:

Sample Information					Tests Required						Comments	
Envirolab Sample ID	Client Sample ID or Information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water							Provide as much information about the sample as you can
1	MCU	100 mm	24/10/2022	Water	✓							MCU 35°43'55" S 150°10'03" E - West
2	HRC1	100 mm	24/10/2022	Water	✓							HRC1 (1) 35°43'47" S 150°10'33" E - Bridge
3	HRC2	100 mm	24/10/2022	Water	✓							HRC2 (2) 35°43'47" S 150°10'33" E - Track
4	MCU	100 mm	25/10/2022	Water	✓							MCU 35°43'55" S 150°10'03" E - West
5	HRC1	100 mm	25/10/2022	Water	✓							HRC1 (1) 35°43'47" S 150°10'33" E - Bridge
6	HRC2	100 mm	25/10/2022	Water	✓							HRC2 (2) 35°43'47" S 150°10'33" E - Track


Envirolab Services
 12 Ashley St
 Chatswood NSW 2067
 Ph: (02) 9910 6200
Job No: 30 90 73
Date Received: 27/10/22
Time Received: 09:20
Received By: [Signature]
Temp: Cool/Ambient
Cooling: Ice/Icepack
Security: Intact/Broken/None 22°C

Relinquished by (Company): Transport for NSW	Received by (Company): <u>ELS Sydney</u>	Lab use only:
Print Name: Sri Naidu	Print Name: <u>Alstemon</u>	Samples Received: Cool or <u>Ambient</u> (circle one)
Date & Time: 25/10/2022	Date & Time: 27/10/22 0920	Temperature Received at: 22°C (if applicable)
Signature: [Signature]	Signature: [Signature]	Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 316398

Client Details

Client	Transport for NSW
Attention	Sri Naidu
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	2 Water
Date samples received	13/02/2023
Date completed instructions received	13/02/2023

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 20/02/2023

Date of Issue 20/02/2023

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Priya Samarawickrama, Senior Chemist

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics			
Our Reference		316398-1	316398-2
Your Reference	UNITS	MCU	HRCD1
Depth		70	70
Date Sampled		10/02/2023	26/09/2022
Type of sample		Water	Water
Date prepared	-	16/02/2023	16/02/2023
Date analysed	-	16/02/2023	16/02/2023
Total Suspended Solids	mg/L	9	<5

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			16/02/2023	[NT]	[NT]	[NT]	[NT]	16/02/2023	[NT]
Date analysed	-			16/02/2023	[NT]	[NT]	[NT]	[NT]	16/02/2023	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	[NT]	[NT]	[NT]	[NT]	96	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.



CHAIN OF CUSTODY - Client

ENVIROLAB GROUP - National phone number 1300 42 43 44

Sydney Lab - Envirolab Services
12 Ashley St, Chatswood, NSW 2067
Ph 02 9910 6200 / sydney@envirolab.com.au

Perth Lab - MPL Laboratories
16-18 Hayden Crt Myaree, WA 6154
Ph 08 9317 2505 / lab@mpl.com.au

Melbourne Lab - Envirolab Services
1A Dalmore Drive Scoresby VIC 3179
Ph 03 9763 2500 / melbourne@envirolab.com.au

Brisbane Office - Envirolab Services
20a, 10-20 Depot St, Banyo, QLD 4014
Ph 07 3266 9532 / brisbane@envirolab.com.au

Adelaide Office - Envirolab Services
7a The Parade, Norwood, SA 5067
Ph 0406 350 706 / adelaide@envirolab.com.au

Client: Transport for NSW - Chris Bearzatto
Contact Person: Sri Naidu
Project Mgr: Chris Bearzatto
Sampler: Sri Naidu
Address: 153 Auckland Street, Bega NSW 2550
Phone: (02) 6492 9505 Mob: 0438 636 492
Email: is.Bearzatto@transport.nsw.gov.au - sri.naidu@transport.nsw.gov.au

Client Project Name / Number / Site etc (ie report title):
Batemans Bay Link Road
PO No.: Credit Card
Envirolab Quote No.: Quote request issued 17/12 to D. Springer
Date results required: Standard Testing Time
Or choose: standard
Note: Inform lab in advance if urgent turnaround is required - surcharges apply
Report format: esdat / equis /
Lab Comments:

Sample information					Tests Required										Comments				
Envirolab Sample ID	Client Sample ID or information	Depth	Date sampled	Type of sample	Total Suspended Solids in Water														Provide as much information about the sample as you can
1	MCU	70 mm	10/02/2023	Water	✓														MCU 35°43'55" S 150°10'03" E - West
2	HRC1	70 mm	26/09/2022	Water	✓														HRC1 35°43'47" S 150°10'33" E - Bridge

Envirolab Services
12 Ashley St
Chatswood NSW 2067
Ph: (02) 9910 6200
IC ID:
Date Received: 31/03/23
Time Received: 13/2/23
Received By: 1202
Temp: Cool/Ambient
Cooling: Icepack
Security: In good/Broken/None

Relinquished by (Company): Transport for NSW
Print Name: Chris Bearzatto
Date & Time: 10/02/2023
Signature: CB

Received by (Company): ES
Print Name: Ras
Date & Time: 13/2/23 1200
Signature: R

Lab use only:
Samples Received: Cool or Ambient (circle one)
Temperature Received at: 24 (if applicable)
Transported by: Hand delivered / courier



Envirolab Services Pty Ltd

ABN 37 112 535 645

12 Ashley St Chatswood NSW 2067

ph 02 9910 6200 fax 02 9910 6201

customerservice@envirolab.com.au

www.envirolab.com.au

CERTIFICATE OF ANALYSIS 318393

Client Details

Client	Transport for NSW
Attention	Chris Bearzatto
Address	153 Auckland Street, Bega, NSW, 2550

Sample Details

Your Reference	<u>Transport for NSW - Batemans Bay Link Road</u>
Number of Samples	2 Water
Date samples received	10/03/2023
Date completed instructions received	10/03/2023

Analysis Details

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Report Details

Date results requested by 17/03/2023

Date of Issue 17/03/2023

NATA Accreditation Number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025 - Testing. **Tests not covered by NATA are denoted with ***

Results Approved By

Diego Bigolin, Inorganics Supervisor

Authorised By

Nancy Zhang, Laboratory Manager

Client Reference: Transport for NSW - Batemans Bay Link Road

Miscellaneous Inorganics			
Our Reference		318393-1	318393-2
Your Reference	UNITS	MCU	HRCD1
Depth		100	50
Date Sampled		07/03/2023	07/03/2023
Type of sample		Water	Water
Date prepared	-	16/03/2023	16/03/2023
Date analysed	-	16/03/2023	16/03/2023
Total Suspended Solids	mg/L	<5	6

Client Reference: Transport for NSW - Batemans Bay Link Road

Method ID	Methodology Summary
Inorg-019	Suspended Solids - determined gravimetrically by filtration of the sample. The samples are dried at 104+/-5°C.

Client Reference: Transport for NSW - Batemans Bay Link Road

QUALITY CONTROL: Miscellaneous Inorganics				Duplicate				Spike Recovery %		
Test Description	Units	PQL	Method	Blank	#	Base	Dup.	RPD	LCS-W1	[NT]
Date prepared	-			16/03/2023	[NT]	[NT]	[NT]	[NT]	16/03/2023	[NT]
Date analysed	-			16/03/2023	[NT]	[NT]	[NT]	[NT]	16/03/2023	[NT]
Total Suspended Solids	mg/L	5	Inorg-019	<5	[NT]	[NT]	[NT]	[NT]	112	[NT]

Result Definitions

NT	Not tested
NA	Test not required
INS	Insufficient sample for this test
PQL	Practical Quantitation Limit
<	Less than
>	Greater than
RPD	Relative Percent Difference
LCS	Laboratory Control Sample
NS	Not specified
NEPM	National Environmental Protection Measure
NR	Not Reported

Quality Control Definitions

Blank	This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.
Duplicate	This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.
Matrix Spike	A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.
LCS (Laboratory Control Sample)	This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.
Surrogate Spike	Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.
Australian Drinking Water Guidelines recommend that Thermotolerant Coliform, Faecal Enterococci, & E.Coli levels are less than 1cfu/100mL. The recommended maximums are taken from "Australian Drinking Water Guidelines", published by NHMRC & ARMC 2011.	
The recommended maximums for analytes in urine are taken from "2018 TLVs and BEIs", as published by ACGIH (where available). Limit provided for Nickel is a precautionary guideline as per Position Paper prepared by AIOH Exposure Standards Committee, 2016.	
Guideline limits for Rinse Water Quality reported as per analytical requirements and specifications of AS 4187, Amdt 2 2019, Table 7.2	

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: >10xPQL - RPD acceptance criteria will vary depending on the analytes and the analytical techniques but is typically in the range 20%-50% – see ELN-P05 QA/QC tables for details; <10xPQL - RPD are higher as the results approach PQL and the estimated measurement uncertainty will statistically increase.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals (not SPOCAS); 60-140% for organics/SPOCAS (+/-50% surrogates) and 10-140% for labile SVOCs (including labile surrogates), ultra trace organics and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

Where sampling dates are not provided, Envirolab are not in a position to comment on the validity of the analysis where recommended technical holding times may have been breached.

Where matrix spike recoveries fall below the lower limit of the acceptance criteria (e.g. for non-labile or standard Organics <60%), positive result(s) in the parent sample will subsequently have a higher than typical estimated uncertainty (MU estimates supplied on request) and in these circumstances the sample result is likely biased significantly low.

Measurement Uncertainty estimates are available for most tests upon request.

Analysis of aqueous samples typically involves the extraction/digestion and/or analysis of the liquid phase only (i.e. NOT any settled sediment phase but inclusive of suspended particles if present), unless stipulated on the Envirolab COC and/or by correspondence. Notable exceptions include certain Physical Tests (pH/EC/BOD/COD/Apparent Colour etc.), Solids testing, total recoverable metals and PFAS where solids are included by default.

Samples for Microbiological analysis (not Amoeba forms) received outside of the 2-8°C temperature range do not meet the ideal cooling conditions as stated in AS2031-2012.

6 PIRMP Summary

Pollution Incident Response Management Plan - Summary

EPL 21590

Under Part 5.7 of the *Protection of the Environment Operations Act 1997*, there is a duty to notify each relevant authority (identified below) of a pollution incident, where material harm to the environment is caused or threatened. Material harm includes actual or potential harm to the health or safety of human beings or to ecosystems, that is not trivial or that results in actual or potential loss or property damage of an amount over \$10,000.

In the event of a potential pollution incident causing or threatening material harm, and in accordance with the Pollution Incident Response Management Plan project staff will seek immediate assistance from the Works Supervisor and Senior Project Engineer in consultation with the Environment and Sustainability Manager to determine whether notification to the relevant authorities is required. If the site staff listed above are not available, staff will contact the District Works Manager in Bega and the Senior Environment and Sustainability Manager to determine whether notification to the relevant authorities is required. If none of the listed contacts are available, the most senior staff member available will determine whether notification to the relevant authorities is required. If an incident is determined to be Material Harm, the most senior staff member available will advise who will make notification to the relevant authorities, as detailed below.

Relevant Authority Notification	
If the incident presents an immediate threat to human health or property, notification will be undertaken in the following order:	
Fire and Rescue NSW	000
EPA	131 555
Ministry of Health Southern Health District	1800 999 880
Safe Work NSW	131 050
Eurobodalla Shire	02 4474 1000
If there is not an immediate threat to human health or the environment, notification will be undertaken in the following order:	
EPA Environment Line	131 555
Eurobodalla Shire	02 4474 1000
Ministry of Health Southern Health District	1800 999 880
Safe Work NSW	131 050
Fire and Rescue NSW	1300 729 579

Community Advice Mechanisms

Early warnings for affected or potentially affected community members for any pollution incident are to be communicated by methods such as door knocking, letters, signs, notices, local papers, leaflets, etc. (minimum of letter box drop and a clearly visible sign on premises). For air pollution incidents that may affect community members, those community members may be asked to either close their doors and windows and stay indoors until further notice or to vacate the premises. For water pollution incidents that may affect community members, those community members may be asked to avoid use of the water until further notice.

Transport for NSW will provide regular updates of any pollution incidents either via letterbox drop, notices in local papers and/or via door knocks as required.